

EPC-408 TCP/IP Converter

Features



- Supports RS-422 and RS-485 communication interfaces.
- Automatically detect 10 / 100Mbps Ethernet interface.
- High performance data converter between RS-422 / RS-485 & Ethernet
- Supports to set parameters through Web Browser for easy-to-use and maintenance
- Allows to download the configuration parameters or configure IP through the utility program.
- Supports DHCP client
- Supports TCP Server / Client and UDP Server / Client connection mode.
- TCP Server Mode supports Keep Alive Check and the settings to disconnect while remote idle timeout
- TCP Client Mode supports automatic connection mode and data connection mode.
- RS-422/485 support 2400, 4800, 9600, 19200, 38400, 57600, 115200bps baudrate.
- RS-422/485 support even parity, odd parity and no parity check settings.
- Watchdog function secures system free from halting
- Complies with EMS 、EMI test standard

Ordering Information

Package Content:

- EPC-408 x 1
- Software CD x 1

Specifications

Model No.	EPC-408
CPU	32 Bit
Comm. Interface	TCP/IP : 10/100 Mbps Serial : RS-422 / RS-485
Power Input	DC 12V, 150mA (Max)
Comm. Baudrate	2400 、 4800 、 9600 、 19200 、 38400 、 57600 、 115200bps Parity: None, Data bits: 8, Stop bit: 1
Operating Temp.	-40°C ~70°C / -40°F ~158°F
Relative Humidity	20% ~ 80% (Non Condensing)
Dimension(mm)	95 (L) x 62 (W) x 28 (H)
Weight (Device)	80g