

PXR-50 EM Reader



Features

- Support 125 KHz-EM card.
- Reading distances are around 6-8 cm.
- Provides different communication interface with controller.
- Mini-Mullion reader, suitable for being installed on narrow door frame.
- Splash-proof mechanical design.
- Wide operation temperature range, it can be installed in different arctic or tropical regions.
- Case sensor detection function.
- Watchdog function secures system free from halting.

Ordering Information

Package Content:

- PXR-50 x 1
- Quick Start Guide x 1
- Accessory Pack x 1

Model No. Identification

P X R - 5 0 E T

Comm. Interface
T: T2
W: Wiegand
E: EM
Device Type
Product Category

Color

●
Black
(BL)

Specifications

Model No.	PXR-50ET	PXR-50EW
Read Format	EM (125 KHz)	
Read Range	6-8 cm(max)	
Comm. Interface	T2	Wiegand
Input Port	Case Sensor x 1	
LED Indicator	Power / Comm.	
Beep Tone	Buzzer	
Power Input	DC 12V / 1A	
Current Consumption	200mA (max)	
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F	
Relative Humidity	20% ~ 80%(Non-condensing)	
Dimensions (LxWxH)	95 x 44 x 16 (mm)	