

# PXR-50 Mifare Reader



## Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Mini-Mullion reader, suitable for being installed on narrow door frame
- Provides RS-485 communication interface for long distance installation.
- Splash-proof mechanical design.
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Case sensor detection function.
- Watchdog function secures system free from halting.

## Ordering Information

### Package Content:

- PXR-50 x 1
- Quick Start Guide x 1
- Accessory Pack x 1

### Model No. Identification

**P X R - 5 0 M S**

Comm. Interface  
S: RS-485

M: Mifare  
Device Type

Product Category

### Color

●  
Black  
(BL)

## Specifications

Model No.	<b>PXR-50MS</b>
Read Format	Mifare (13.56 MHz)
Read Range	3 cm(max)
Comm. Interface	RS-485
Input Port	Case Sensor x 1
ID Setting	DIP switch setting
Comm. Baudrate	19,200 bps-N-8-1
LED Indicator	Power / Comm.
Beep Tone	Buzzer
Power Input	DC 12V / 1A
Current Consumption	200mA (max)
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F
Relative Humidity	20% ~ 80%(Non-condensing)
Dimensions (LxWxH)	95 x 44 x 16 (mm)