
PXR-52 EM Keypad Reader



Features

- Support 125 KHz-EM card
- Reading distances are around 8~10 cm
- Case sensor detection function
- Watchdog function secures system free from halting
- Provide different communication interface with controller.
- Special model to provide both T2 and Wiegand interface, it allow customer to use more flexible. (PXR-52ETWK)
- Provide RS-485 communication interface, it may suit for long distance installation.(PXR-52ESK)
- Keypad function. When work with controller, it provides swipe card, press keypads or card with password to access.
- Rubber material keypad, with the splash-proof mechanical design.
- Wide operation temperature range, it can be install in different arctic or tropical regions.

Ordering Information



Specifications

Model No.	PXR-52ETWK	PXR-52ESK
Read Format	EM (125 KHz)	
Read Range	8-10 cm(max)	
Comm. Interface	T2 / Wiegand	RS-485
Keypad	12 Key (0-9, CE, Enter)	
Input Port	Case Sensor x 1	
ID Setting	NONE	DIP switch setting
Comm. Baudrate	NONE	19,200 bps-N-8-1
LED Indicator	Power / Comm.	
Beep Tone	Buzzer	
Power Input	DC 12V / 1A	
Current Consumption	200mA (max)	
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F	
Relative Humidity	20% ~ 80%(Non-condensing)	
Dimensions (LxWxH)(mm)	120 x 76 x 23	