

# PXR-52 Mifare Reader



## Features


- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Provide different communication interface with controller.
- Provides RS-485 communication interface for long distance installation.(PXR-52MS)
- Splash-proof mechanical design.
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Case sensor detection function.
- Watchdog function secures system free from halting.

## Ordering Information

### Package Content:

- PXR-52 x 1
- Quick Start Guide x 1
- Accessory Pack x 1

### Model No. Identification



### Color

- Dark Grey (DG)

## Specifications

Model No.	PXR-52MT	PXR-52MW	PXR-52MS
Read Format	Mifare (13.56 MHz)		
Read Range	3-5 cm(max)		
Comm. Interface	T2	Wiegand	RS-485
Input Port	Case Sensor x 1		
ID Setting	NONE		DIP switch setting
Comm. Baudrate	NONE		19,200 bps-N-8-1
LED Indicator	Power / Comm.		
Beep Tone	Buzzer		
Power Input	DC 12V / 1A		
Current Consumption	200mA (max)		
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F		
Relative Humidity	20% ~ 80%(Non-condensing)		
Dimensions (LxWxH)(mm)	120 x 76 x 23		