

PXR-62 Mifare Reader



(SG)



(DG)

Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Provides different communication interface with controller.
- Provides RS-485 communication interface for long distance installation.(PXR-62MS)
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Case sensor detection function.
- Watchdog function secures system free from halting.

Ordering Information

Package Content:

- PXR-62 x 1
- Quick Start Guide x 1
- Accessory Pack x 1

Model No. Identification

P X R - 6 2 M T

Comm. Interface
T: T2
W: Wiegand
S: RS-485
M: Mifare
Device Type
Product Category

Color

 Silver Grey (SG)
 Dark Grey (DG)

Specifications

Model No.	PXR-62MT	PXR-62MW	PXR-62MS
Read Format	Mifare (13.56 MHz)		
Read Range	3-5 cm(max)		
Comm. Interface	T2	Wiegand	RS-485
Input Port	Case Sensor x 1		
ID Setting	NONE		DIP switch setting
Comm. Baudrate	NONE		19,200 bps-N-8-1
LED Indicator	Power / Comm.		
Beep Tone	Buzzer		
Power Input	DC 12V / 1A		
Current Consumption	200mA (max)		
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F		
Relative Humidity	20% ~ 80%(Non-condensing)		
Dimensions (LxWxH)(mm)	120 x 76 x 27		