

# PXR-71 EM Keypad Reader



## Features

- Narrow mullion design is pretty suitable for installing on door frame or in tight space.
- Supports EM (125KHz) card.
- Provided a case sensor switch, it can be connected to the controller and operated by the controller.
- Reader's LED & Buzzer controls can be set by upstream control panel.
- Equipped with a 12-key keypad with white backlight.
- IP65 rated ingress protection, suitable to install indoor and outdoor environments. (PXR-71EWK-WR)
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Watchdog function secures system free from halting.

## Ordering Information

### Package Content:

- Reader x 1
- Accessory Pack x 1
- Quick Start Guide x 1

### Model No. Identification

**P X R - 7 1 E W K - W R**

- Water Resistant
- Keypad
- Wiegand
- EM
- Device Type
- Product Category

### Color

●  
Light Gray  
(LG)

## Specifications

Model No.	PXR-71EWK	PXR-71EWK-WR
Read Format	EM (125 KHz)	EM (125 KHz)
Read Range	2 cm	2 cm
Comm. Interface	Wiegand	Wiegand
Input Ports	LED Control × 1, Buzzer Control × 1	LED Control × 1, Buzzer Control × 1
Output Port	Case Sensor x 1, Wiegand x 1	Case Sensor x 1, Wiegand x 1
LED Indicator	Read / Green Bi-color LED x 1 (Status / Power)	Read / Green Bi-color LED x 1 (Status / Power)
Keypad	12 Keys (0~9, *, #)	12 Keys (0~9, *, #)
Real Time Clock	Yes	Yes
Beep Tone	Buzzer	Buzzer
Ingress Protection	N/A	IP65
Power Input	DC 12V	DC 12V
Current Consumption	300mA (max.)	300mA (max.)
Operating Temp.	20°C ~ 70°C / -4°F ~ 158°F	20°C ~ 70°C / -4°F ~ 158°F
Relative Humidity	20% ~ 80% (Non-condensing)	20% ~ 80% (Non-condensing)
Dimension (mm)	130 (L) x 45 (W) x 25 (H)	130 (L) x 45 (W) x 25 (H)