

PXR-92 EM Keypad Reader



Features

- Support 125 KHz-EM card
- Reading distances are around 8~10 cm
- Slim, stylish design, sensitive touch keypad with blue backlight.
- Keypad function. When work with controller, it provides swipe card, press card number by keypads or card with password to access.
- Case sensor detection function
- Watchdog function secures system free from halting
- Provide different communication interface with controller.
- Special model to provide both T2 and Wiegand interface, it allows customer to use more flexibly. (PXR-92ETWK)
- Provide RS-485 communication interface, it may suit for long distance installation. (PXR-92ESK)
- IP65 waterproof and dustproof testing, easy to install indoor and outdoor environments.
- Wide operation temperature range, it can be installed in different arctic or tropical regions.

Ordering Information

Package Content:

- PXR-92 x 1
- Accessory Pack x 1
- Quick Start Guide x 1
- Plate x 1

Model No. Identification

PXR-92ETK— Keypad

- Comm. Interface
- T: T2
- W: Wiegand
- TW: T2 / Wiegand
- S: RS-485
- E: EM
- Device Type
- Product Category

Color

●
Black
(BL)

Specifications

Model No.	PXR-92ETK	PXR-92EWK	PXR-92ETWK	PXR-92ESK
Read Format	125 KHz (EM Compatible)			
Read Range	8-10 cm(max)			
Comm. Interface	T2	Wiegand	T2 / Wiegand	RS-485
Keypad	12 Key(0-9, *, #)			
Input Port	Case Sensor x 1			
ID Setting	NONE			DIP switch setting
Comm. Baudrate	NONE			19,200 bps-N-8-1
LED Indicator	Power / Comm.			
Beep Tone	Buzzer			
Ingress Protection	IP 65			
Power Input	DC 12V / 1A			
Current Consumption	200mA (max)			
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F			
Relative Humidity	20% ~ 80%(Non-condensing)			
Dimension (LxWxH)(mm)	120 x 77 x 22			