

PXR-92 Mifare Keypad Reader



Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Slim, stylish design, capacitive touch keypad with blue backlight.
- Keypad function. When working with controller, it provides unlock modes including card-swiping, pressing card number by keypad or card-swiping with password to access
- If the keypad function is disabled but under the entry mode of card-swiping with password, the keypad will be enabled automatically after swiping card and then disabled again after keypad operation.
- Provides different communication interfaces to connect with controllers for different site applications
- Provides RS-485 communication interface for long distance installation (PXR-92MSK)
- IP65 rated ingress protection, suitable to install indoor and outdoor environments.
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Case sensor detection function to enhance the system security.
- Watchdog function secures system free from halting.

Ordering Information

Package Content:

- PXR-92 x 1
- Accessory Pack x 1
- Quick Start Guide x 1
- Plate x 1

Model No. Identification

PXR-92MTK – Keypad

- T: T2
- W: Wiegand
- S: RS-485
- M: Mifare
- Device Type
- Product Category

Color

●
Black
(BL)

Specifications

Model No.	PXR-92MTK	PXR-92MWK	PXR-92MSK
Read Format	Mifare (13.56 MHz)		
Read Range	3-5 cm(max)		
Comm. Interface	T2	Wiegand	RS-485
Keypad	12 Key(0-9, *, #)		
Input Port	Case Sensor x 1		
ID Setting	None		DIP switch setting
Comm. Baudrate	None		19,200 bps-N-8-1
LED Indicator	Power / Comm.		
Beep Tone	Buzzer		
Ingress Protection	IP 65		
Power Input	DC 12V / 1A		
Current Consumption	200mA (max)		
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F		
Relative Humidity	20% ~ 80%(Non-condensing)		
Dimension (LxWxH)(mm)	120 x 77 x 22		