

# PXR-93 Mifare Reader



## Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Provides different communication interfaces to connect with controllers for different site applications
- Provides RS-485 communication interface for long distance installation. (PXR-93MS)
- IP65 rated ingress protection, suitable to install indoor and outdoor environments.
- Wide range of operating temperature to meet the requirements of tropical or frigid zone climate environment.
- Case sensor detection function to enhance the system security.

## Ordering Information

### Package Content:

- PXR-93 x 1
- Accessory Pack x 1
- Quick Start Guide x 1
- Plate x 1

### Model No. Identification

**P X R - 9 3 M T**

Comm. Interface

T: T2

W: Wiegand

S: RS-485

M: Mifare

Device Type

Product Category

### Color



Silver  
(SV)

## Specifications

Model No.	PXR-93MT	PXR-93MW	PXR-93MS
Read Format	Mifare (13.56 MHz)		
Read Range	3-5 cm(max)		
Comm. Interface	T2	Wiegand	RS-485
Input Port	Case Sensor x 1		
ID Setting	None		DIP switch setting
Comm. Baudrate	None		19,200 bps-N-8-1
LED Indicator	Power / Comm.		
Beep Tone	Buzzer		
Ingress Protection	IP 65		
Power Input	DC 12V / 1A		
Current Consumption	200mA (max)		
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F		
Relative Humidity	20% ~ 80%(Non-condensing)		
Dimension (LxWxH)(mm)	120 x 77 x 22		