

PXR-66MSL Reader



(SG)



(DG)

Features

- Conforms to ISO 14443A, supporting MIFARE card.
- Unique ID or Block read format supported and programmable key value.
- Flush mounted design, compact & slim dimensions, working with 86-type back box to minimize the exposed part ; Suitable for matching interior design
- Provides RS-485 communication interface for long distance installation.
- The ability to automatically detect the connection status with the control panel. While disconnecting from the control panel, it can still working properly under auto learning mode
- Auto-Learning function. Auto memory of 470 cards' capacity to temporarily work as standalone operation mode once the reader disconnects from the control panel
- Wide operation temperature range; It can be installed in extreme cold or hot regions.
- Watchdog function secures system free from halting.

Ordering Information

Package Content:

- PXR-66 x 1
- Quick Start Guide x 1
- Plate x 1
- Accessory Pack x 1

Model No. Identification

P X R - 6 6 M S L

— L: Auto-Learning
— S: RS-485
— M: MIFARE®
— Device Type
— Product Category

Color

Dark Grey (DG) Silver Grey (SG)

Specifications

Model No.	PXR-66MSL
Read Format	Mifare (13.56 MHz)
Read Range	3 cm(max)
Comm. Interface	RS-485
Input Ports	2 Sensors (Door Sensor x 1 、 Exit Button x 1)
Output Ports(Built-in)	Relay x 1 (Door Lock)
Output Ports(External)	O.C. Output x 2 (Door Lock / Alarm, external ACU-30/90)
ID Setting	DIP switch setting
Comm. Baudrate	19,200 bps-N-8-1
LED Indicator	Power / Comm.
Beep Tone	Buzzer
Power Input	DC 12V / 1A
Current Consumption	200mA (max)
Operating Temp.	-10°C~ 70°C / 14°F~ 158°F
Relative Humidity	20% ~ 80%(Non-condensing)
Dimensions (LxWxH)(mm)	86 x 86 x 28